

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
21 May 2004 (21.05.2004)


PCT

(10) International Publication Number
WO 2004/041038 A1

- (51) International Patent Classification⁷: **A47J 31/04** (74) Agent: CHAS. HUDE A/S; 33, H.C. Andersens Boulevard, DK-1780 Copenhagen V (DK).
- (21) International Application Number: PCT/DK2003/000677 (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 9 October 2003 (09.10.2003) (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (25) Filing Language: Danish
- (26) Publication Language: English
- (30) Priority Data: PA 2002 01516 9 October 2002 (09.10.2002) DK
- (71) Applicant (*for all designated States except US*): PI-DESIGN AG [CH/CH]; Kantonsstrasse 100, Postfach 463, CH-6234 Triengen (CH).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): JØRGENSEN, Carsten [DK/CH]; St. Niklausen Strasse 17, CH-6005 St. Niklausen/LU (CH).

[Continued on next page]

(54) Title: ADJUSTABLE ASCENSION PIPE



(57) Abstract: Adjustable riser pipe to be used for instance in a coffee maker with two containers sealingly arranged relative to and above one another, said two containers being flow-connected through the adjustable riser pipe in such a manner that liquid water can be caused to leave the closed lower container and enter the upper container through said riser pipe by means of pressure resulting from a heating until the rising of liquid water is stopped because the water level reaches a limit level defined by a level set by the lower edge of the riser pipe. The Adjustable riser pipe (7) according to the invention is formed by a main pipe (2) and by a sleeve (6) being substantially sealingly and axially and axially and/or circumferentially displaceable about said main pipe. The main pipe (2) fixedly and tightly abuts a structure (4) in the upper container (1) at an unchangeable distance from said upper container and in a direction towards the lower edge (5) of the main pipe. The adjustable length of the riser pipe (7) and consequently the set limit for the rising liquid water from the lower container during the brewing procedure are defined by the instantaneous maximum level of the lower edge (8) of the sleeve (6). The advantages are an easy setting by one hand and a high tolerance towards lime deposits.